

AD-A080 062 ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND WS--ETC F/G 4/2
19304D GSRS, MISSILE NUMBER 1063, ROUND NUMBER V-67, 29 AUGUST --ETC(U)
AUG 79


UNCLASSIFIED ERADCOM/ASL-DR-1058

NL

| OF |
ADA
080062



END
DATE
FILMED
2-80
DDC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DR 1058
AUGUST 1979
AD

AD A 080062

LEVEL

12

METEOROLOGICAL DATA REPORT

19304 D GSRS
Missile No. 1063
Round No. V-67
29 August 1979

DDC
RECEIVED
JAN 31 1980
E

by

White Sands Meteorological Team

17073 391

DDC FILE COPY

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND

80 1 30 014

DISPOSAL INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government endorsement or approval of commercial products or services referenced herein.

REPORT DOCUMENTATION PAGE

1. REPORT NUMBER DR 1059		2. GOVT ACCESSION NO.		3. READ INSTRUCTIONS BEFORE COMPLETING FORM 4. DOCUMENT ATATION NUMBER	
5. TITLE (and Subtitle) (6) 19304 D GSRS, Missile Number 1663, Round Number V-67, 29 August 1979.		6. AUTHOR White Sands Meteorological Team		7. PERFORMING ORG. REPORT NUMBER	
8. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Electronics Research & Development Comd Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico 88002		9. CONTRACT OR GRANT NUMBER 16 DA Task 1P665702D127-02		10. DATE OF REPORT 17 02	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Research & Development Comd Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico 88002		12. REPORT DATE August 1979		13. NUMBER OF PAGES 19	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) US Army Electronics Research & Development Comd.		15. SECURITY CLASS. (of this report) UNCLASSIFIED		16. DECLASSIFICATION DOWNGRADING SCHEDULE	
17. DISTRIBUTION STATEMENT (for this report) (12) 19 Approved for public release; distribution unlimited.					
18. DISTRIBUTION STATEMENT (if the abstract entered in block 20, it different from report) (9) Meteorological data rept.					
19. SUPPLEMENTARY NOTES (14) ERADCOM/ASL-DR-1058					
20. KEY WORDS (Continue on reverse side if necessary and identify by block number) 1. Ballistics 2. Meteorology 3. Wind					
21. ABSTRACT (Continue on reverse side if necessary and identify by block number) Meteorological data gathered for the launching of 19304 D GSRS, Missile NR. 1063, Round Number V-67, are presented in tabular form.					

410 663

JSM

CONTENTS	PAGE
INTRODUCTION-----	1
DISCUSSION-----	1
MAP-----	2
TABLES	
1. Surface Observation Taken at 1100 MDT at LC-33-----	3
2. Anemometer-Measured Wind Speed and Direction, LC-33 Fixed Pole, Taken at 1100 MDT-----	4
3. Anemometer-Measured Wind Speed and Direction, Tower Levels 1, 2, 3, and 4, taken at 1100 MDT-----	5
4. Pilot Balloon Measured Wind Data at 1107 MDT-----	6
5. SMR Significant Level Data at 1000 MST-----	8
6. SMR Upper Air at 1000 MST-----	10
7. SMR Mandatory Levels at 1000 MST-----	15

Accession For	
NTIS GRA&I	
DDC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special
A	

INTRODUCTION

19304D GSRS, Missile Number 1063, Round Number V-67, was launched from LC-33, White Sands Missile Range (WSMR), New Mexico, at 1100 MDT, 29 August 1979. The scheduled launch time was 1100 MDT.

DISCUSSION

Meteorological data were recorded and reduced by the White Sands Meteorological Team, Atmospheric Sciences Laboratory (ASL), White Sands Missile Range, New Mexico. The data were obtained by the following methods:

1. Observations

a. Surface

(1) Standard surface observations to include pressure, temperature ($^{\circ}\text{C}$), relative humidity, dew point ($^{\circ}\text{C}$), density (gm/m^3), wind direction and speed, and cloud cover were made at the LC-33 Met Site at T-0 minutes.

(2) Anemometer data were provided from existing pole-mounted and tower-mounted anemometers at LC-33. Monitor of wind speed and direction from one anemometer was also provided in the launch control room.

b. Upper Air

(1) Low level wind data were obtained from RAPTS T-9 pibal observation at:


SITE AND ALTITUDE

SMR 2400 Meters

(2) Air structure data (rawinsonde) were collected at the following Met Sites. Data were collected from surface to 101,500 feet in 500-foot increments.

SITE AND TIME

SMR 1000 MST



1. MET TOWER - 4 Bendix Model T-20 Anemometers at 12 ft, 62 ft, 102 ft, and 202 ft with E/A recorders.
2. POLE ANEMOMETER - Bendix Model T-120 with E/A recorders.
 - (a) Pole #1 - 38.7 ft
 - (b) Pole #2 - 53.0 ft
 - (c) Pole #3 - 83.6 ft
3. RAPTS T-9 Radar Automatic Pilot-Balloon Tracking System T-9 Radar.

TABLE 1. Surface Observations Taken at 1100 MDT,
29 August 1979, at LC-33, 19304D GSRS,
Missile Number 1063, Round Number V-67.

ELEVATION	3,977.30	FT/MSL
PRESSURE	877.7	MBS
TEMPERATURE	27.0	°C
RELATIVE HUMIDITY	39	%
DEW POINT	11.8	°C
DENSITY	1,011	GM/M ³
WIND SPEED	01	MPH
WIND DIRECTION	310	DEGREES
CLOUD COVER	1	Cu
CLOUD COVER	2	Ci

TABLE 2. LC-33 FIXED POLE ANEMOMETER-MEASURED WINDS

POLE #1			POLE #2			POLE #3		
T-TIME SEC	DIR DEG	SPEED MPH	T-TIME SEC	DIR DEG	SPEED MPH	T-TIME SEC	DIR DEG	SPEED MPH
-30	M	5.0	-30	003	2.0	-30	008	7.0
-20	M	4.0	-20	352	3.0	-20	005	5.0
-10	M	4.0	-10	335	3.0	-10	346	4.0
0.0	M	4.0	0.0	357	2.0	0.0	321	6.0
+10	M	4.0	+10	360	3.0	+10	328	5.0

Type 19304D GSRS, Missile No. 1063, Round No. V-67 launched
from LC-33 on 29 August 1979 at 1100 MDT.

POLE #1 = X485,874.29 Y185,958.90 H4018.74 38.7 ft. AGL

POLE #2 = X485,874.93 Y186,012.00 H4033.57 53.0 ft. AGL

POLE #3 = X485,877.29 Y186,116.06 H4063.92 83.6 ft. AGL

NOTE: WIND DIRECTIONS ARE REFERENCED TRUE NORTH.

TABLE 3. LC-33 METEOROLOGICAL TOWER ANEMOMETER-MEASURED WINDS (202 FT. TOWER)

LEVEL #1 12 ft.			LEVEL #2 62 ft.		
T-TIME SEC	DIR DEG	SPEED MPH	T-TIME SEC	DIR DEG	SPEED MPH
-30	357	5.0	-30	332	5.0
-20	347	5.0	-20	337	6.0
-10	338	5.0	-10	344	6.0
0.0	351	4.0	0.0	340	4.0
+10	356	4.0	+10	340	4.0
LEVEL #3 102 ft.			LEVEL #4 202 ft.		
T-TIME SEC	DIR DEG	SPEED MPH	T-TIME SEC	DIR DEG	SPEED MPH
-30	352	6.0	-30	347	5.5
-20	347	6.0	-20	347	5.5
-10	352	5.5	-10	346	5.5
0.0	350	4.5	0.0	345	5.0
+10	354	4.0	+10	335	5.0

WTSM Coordinates: X484,982.64 Y185,957.73 H3983.00 (base)

Type 19304D GSRS, Missile No. 1063, Round No. V-67 launched
from LC-33 on 29 August 1979 at 1100 MDT.

NOTE: WIND DIRECTIONS ARE REFERENCED TRUE NORTH.

PILOT BALLOON MEASURED WIND DATA

TABLE 4

RELEASED FROM LC-33 DATE 29 August 1979 TIME 1107 MDT

RELEASE POINT COORDINATES (WSTM) X=486,037.24 Y=182.350.16 H=3,977.3

MISSILE TYPE 19304 D GPRS MISSILE NO. 1063 ROUND NO. V-67

MISSILE LAUNCHED FROM LC-33 DATE 29 AUGUST 1979 TIME 1100 MDT

NOTE: WIND DIRECTIONS ARE REFERENCED TRUE NORTH.

HEIGHTS - METERS AGL.

HEIGHT AGL	DIRECTION DEGREES	SPEED MPH
SFC	310	01.0
60	310	01.0
120	324	03.0
180	326	05.0
240	327	07.5
300	350	09.0
360	006	12.0
420	013	14.0
480	009	11.0
540	002	08.0
600	357	06.0
660	355	05.5
720	353	04.5
780	352	03.0
840	349	01.5

HEIGHT AGL	DIRECTION DEGREES	SPEED MPH
900	359	00.5
960	083	00.5
1020	106	01.0
1080	101	01.5
1140	092	01.5
1200	085	01.5
1260	079	01.5
1320	073	01.5
1380	054	01.0
1440	032	01.5
1500	040	03.0
1560	052	08.0
1620	055	13.0
1680	053	10.5
1740	046	06.5

MDT

[illegible][illegible]

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79
ASLENSION NO. 284

SIGNIFICANT LEVEL DATA

2410060284

S M R

TABLE 5

GEODETIC COORDINATES
32.48034 LAT DEG
106.42307 LONG DEG

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE		REL. HUM. PERCENT
		AIR DEGREES	DEWPOINT CENTIGRADE	
877.0	3997.3	28.0	6.7	26.0
850.0	4900.3	23.6	6.4	33.0
773.0	7606.5	20.4	.3	26.0
744.4	8670.7	18.2	-.1	29.0
700.0	10386.3	13.6	-2.3	33.0
679.6	11201.6	11.5	-5.4	30.0
617.0	13822.8	4.4	-5.1	50.0
549.2	16894.5	-3.9	-8.5	70.0
532.0	17718.0	-6.0	-12.3	61.0
522.4	18186.8	-6.7	-11.4	59.0
516.8	18463.8	-6.7	-18.0	40.0
508.8	18804.2	-7.3	-13.5	61.0
500.0	19311.1	-7.9	-16.0	52.0
485.2	20078.8	-8.5	-24.5	26.0
462.2	21311.2	-11.4	-18.8	34.0
447.2	22142.5	-12.4	-20.9	49.0
400.0	24915.2	-18.4	-26.0	51.0
379.9	26174.5	-21.4	-26.2	55.0
362.2	27329.6	-22.9	-30.6	48.0
329.6	29579.9	-28.6	-45.4	18.0
303.0	31545.1	-33.4	-37.4	57.0
300.0	31775.0	-33.8	-39.3	19.0
289.2	32622.2	-33.4	-49.0	
275.0	33782.2	-35.2		
250.0	35944.7	-40.7		
200.0	40824.1	-52.4		
173.4	43813.8	-59.9		
164.6	44885.0	-60.4		
150.0	46778.5	-63.7		
125.6	50321.4	-69.4		
115.0	52056.8	-69.5		
111.6	52649.8	-67.8		
105.0	53849.2	-71.3		
100.0	54801.8	-71.0		
89.8	56911.3	-69.6		
70.0	61924.8	-60.4		
50.0	68891.3	-57.9		
39.6	73774.2	-55.8		
30.0	79698.1	-49.9		
24.4	84167.9	-49.9		

GEODETIC COORDINATES
32.48034 LAT DEG
106.42307 LON DEG

SIGNIFICANT LEVEL DATA
2410060284
S M R
TABLE 5 (CONT)

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79
ASCENSION NO. 284

PRESSURE	GEOMETRIC	TEMPERATURE	REL. HUM.
MILLIBARS	ALTITUDE	AIR	PERCENT
	MSL FEET	DEWPOINT	
		DEGREES	
		CENTIGRADE	
20.0	88514.1	-45.5	
15.6	94018.1	-44.0	
11.0	101905.0	-37.1	

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79 1000 HRS MST
ASCENSION NO. 284

UPPER AIR DATA
2410060264
S M R
TABLE 6

GEODETIC COORDINATES
32.48034 LAT DEG
106.42307 LON DEG

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
3997.3	877.0	28.0	26.0	1010.2	677.5	60.0	8.0	1.000266
4000.0	876.9	28.0	26.0	1010.1	677.5	60.0	8.0	1.000266
4500.0	861.9	25.6	29.9	1000.8	674.8	51.7	6.3	1.000265
5000.0	847.0	23.5	32.7	990.5	672.4	37.8	4.8	1.000262
5500.0	832.3	22.9	31.4	975.5	671.6	14.4	3.8	1.000255
6000.0	817.8	22.3	30.2	960.7	670.9	13.5	2.9	1.000249
6500.0	803.6	21.7	28.9	946.1	670.1	16.7	2.0	1.000244
7000.0	789.6	21.1	27.6	931.7	669.4	358.4	1.5	1.000238
7500.0	775.9	20.5	26.3	917.5	668.7	337.9	1.4	1.000232
8000.0	762.3	19.6	27.1	904.4	667.6	328.5	1.7	1.000229
8500.0	748.9	18.6	28.5	891.6	666.4	358.7	2.0	1.000226
9000.0	735.7	17.3	29.8	879.6	665.0	23.5	2.9	1.000222
9500.0	722.6	16.0	30.9	868.1	663.4	28.0	4.4	1.000219
10000.0	709.8	14.6	32.1	856.7	661.8	27.9	5.3	1.000215
10500.0	697.1	13.3	32.6	845.5	660.3	25.6	5.7	1.000211
11000.0	684.6	12.0	30.7	834.3	658.7	32.7	5.7	1.000206
11500.0	672.2	10.7	32.3	823.0	657.1	45.0	5.5	1.000203
12000.0	659.9	9.3	36.1	811.8	655.6	60.1	5.9	1.000201
12500.0	647.8	8.0	39.9	800.8	654.0	73.0	6.6	1.000199
13000.0	636.0	6.6	43.7	789.9	652.5	89.1	7.3	1.000197
13500.0	624.4	5.3	47.5	779.2	650.9	101.9	8.5	1.000194
14000.0	612.9	3.9	51.2	768.6	649.3	112.0	10.4	1.000192
14500.0	601.4	2.6	54.4	757.9	647.7	118.4	12.1	1.000189
15000.0	590.1	1.2	57.7	747.4	646.1	122.3	13.4	1.000186
15500.0	579.0	-0.1	60.9	737.0	644.5	129.7	14.1	1.000183
16000.0	568.1	-1.5	64.2	726.8	642.9	131.7	14.4	1.000180
16500.0	557.5	-2.8	67.4	716.8	641.2	134.6	13.8	1.000177
17000.0	547.0	-4.2	68.8	706.9	639.6	137.0	12.9	1.000174
17500.0	536.5	-5.4	63.4	696.9	638.0	143.9	11.2	1.000169
18000.0	526.2	-6.4	65.8	686.0	636.8	154.1	9.9	1.000166
18500.0	516.1	-6.8	67.4	674.1	636.2	168.7	10.2	1.000158
19000.0	506.1	-7.5	58.3	662.6	635.5	177.8	11.0	1.000159
19500.0	496.3	-8.0	45.6	651.4	634.7	179.2	11.7	1.000153
20000.0	486.7	-8.4	28.7	640.0	634.1	178.9	11.7	1.000148
20500.0	477.2	-9.5	35.6	630.0	632.8	177.1	11.3	1.000146
21000.0	467.9	-10.7	46.9	620.4	631.5	177.2	11.2	1.000145
21500.0	458.7	-11.6	52.9	610.4	630.4	177.7	11.2	1.000143
22000.0	449.7	-12.2	49.9	599.9	629.8	177.2	11.8	1.000140
22500.0	440.8	-13.2	49.3	590.1	628.4	177.3	12.3	1.000138
23000.0	432.0	-14.3	49.6	580.8	627.1	179.9	12.2	1.000135

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79 1000 HRS MST
ASCENSION NO. 284

UPPER AIR DATA
2410060284
S M R
TABLE 6 (CONT)

GEODETTIC COORDINATES
32.48034 LAT DEG
106.42307 LON DEG

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
23500.0	423.4	-15.3	50.0	571.7	625.8	184.1	12.3	1.000133
24000.0	415.0	-16.4	50.3	562.7	624.5	190.7	12.8	1.000130
24500.0	406.7	-17.5	50.7	553.8	623.1	197.6	13.7	1.000128
25000.0	398.6	-18.6	51.9	545.2	621.8	203.9	15.2	1.000126
25500.0	390.5	-19.8	57.5	536.6	620.3	209.5	16.4	1.000124
26000.0	382.6	-21.0	63.1	528.2	618.9	214.4	17.5	1.000122
26500.0	374.8	-21.8	60.2	519.2	617.8	216.1	16.9	1.000119
27000.0	367.2	-22.5	52.9	510.0	617.0	216.8	15.5	1.000117
27500.0	359.6	-23.3	45.7	501.3	615.9	216.5	13.9	1.000114
28000.0	352.2	-24.6	39.1	493.4	614.3	215.9	12.2	1.000112
28500.0	344.9	-25.9	32.4	485.7	612.7	220.7	13.0	1.000110
29000.0	337.7	-27.1	25.7	478.1	611.1	225.3	14.2	1.000108
29500.0	330.7	-28.4	19.1	470.6	609.5	230.0	16.5	1.000106
30000.0	323.7	-29.6	28.5	463.0	608.0	233.1	18.9	1.000104
30500.0	316.9	-30.8	40.9	455.5	606.5	232.5	20.7	1.000103
31000.0	310.2	-32.1	53.4	448.1	605.0	232.6	22.6	1.000101
31500.0	303.6	-33.3	65.9	440.8	603.4	235.6	25.2	1.000100
32000.0	297.1	-33.7	46.9	432.1	602.9	238.7	28.6	1.000097
32500.0	290.7	-33.5	24.5	422.5	603.2	243.0	34.1	1.000095
33000.0	284.5	-34.0	12.8**	414.4	602.5	245.3	39.5	1.000093
33500.0	278.4	-34.8	4.6**	406.8	601.5	245.9	44.3	1.000091
34000.0	272.4	-35.8		399.7	600.2	246.3	48.6	1.000069
34500.0	266.4	-37.0		393.1	598.6	246.4	52.1	1.000088
35000.0	260.6	-38.3		386.6	597.0	247.3	54.1	1.000086
35500.0	254.9	-39.6		380.2	595.4	248.9	54.9	1.000085
36000.0	249.4	-40.8		373.9	593.8	250.4	54.6	1.000083
36500.0	243.7	-42.0		367.4	592.3	251.9	53.6	1.000082
37000.0	238.2	-43.2		360.9	590.7	253.5	54.2	1.000080
37500.0	232.8	-44.4		354.6	589.2	255.0	55.3	1.000079
38000.0	227.6	-45.6		348.4	587.6	253.9	56.1	1.000078
38500.0	222.4	-46.8		342.4	586.1	252.2	56.8	1.000076
39000.0	217.4	-48.0		336.4	584.5	249.6	56.9	1.000075
39500.0	212.5	-49.2		330.6	583.0	247.2	57.0	1.000074
40000.0	207.7	-50.4		324.8	581.4	247.2	55.9	1.000072
40500.0	203.0	-51.6		319.2	579.8	249.3	53.9	1.000071
41000.0	198.3	-52.8		313.6	578.2	250.0	53.5	1.000070
41500.0	193.7	-54.1		308.0	576.6	249.3	54.4	1.000069
42000.0	189.1	-55.3		302.4	575.9	249.0	53.6	1.000067
42500.0	184.6	-56.6		297.0	573.3	249.1	51.4	1.000066
43000.0	180.3	-57.9		291.7	571.6	249.3	48.4	1.000065

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79 1000 HRS MST
ASCENSION NO. 284

UPPER AIR DATA
24100-0284
S M R
TABLE 6 (CONT)

GEODETTIC COORDINATES
32.48034 LAT DEG
106.42307 LON DEG

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	INDEX OF REFRACTION
43500.0	176.0	-59.1		286.5	570.0	249.8	1.000064
44000.0	171.8	-60.0		280.8	568.8	250.2	1.000063
44500.0	167.7	-60.2		274.4	568.5	240.2	1.000061
45000.0	163.7	-60.6		268.3	568.0	241.9	1.000060
45500.0	159.7	-61.5		262.8	568.8	238.2	1.000059
46000.0	155.8	-62.3		257.5	568.6	234.4	1.000057
46500.0	152.1	-63.2		252.3	568.5	232.7	1.000056
47000.0	148.3	-64.1		247.2	568.3	232.9	1.000055
47500.0	144.7	-64.9		242.0	562.2	234.1	1.000054
48000.0	141.1	-65.7		236.9	561.2	237.5	1.000053
48500.0	137.6	-66.5		231.9	560.1	241.3	1.000052
49000.0	134.2	-67.3		227.1	559.0	242.3	1.000051
49500.0	130.9	-68.1		222.3	557.9	243.5	1.000050
50000.0	127.6	-68.9		217.7	556.8	245.2	1.000048
50500.0	124.5	-69.4		212.8	556.1	247.5	1.000047
51000.0	121.3	-69.4		207.5	556.0	248.3	1.000046
51500.0	118.3	-69.5		202.3	556.0	243.9	1.000045
52000.0	115.3	-69.5		197.3	556.0	238.4	1.000044
52500.0	112.4	-68.2		191.2	557.7	230.8	1.000043
53000.0	109.6	-68.8		186.9	556.9	222.1	1.000042
53500.0	106.9	-70.3		183.5	554.9	213.5	1.000041
54000.0	104.2	-71.3		179.8	553.6	211.3	1.000040
54500.0	101.6	-71.1		175.1	553.8	208.8	1.000039
55000.0	99.0	-70.9		170.5	554.1	200.3	1.000038
55500.0	96.5	-70.5		165.9	554.5	188.9	1.000037
56000.0	94.1	-70.2		161.5	555.0	179.5	1.000036
56500.0	91.7	-69.9		157.2	555.4	175.3	1.000035
57000.0	89.4	-69.4		152.9	556.0	171.7	1.000034
57500.0	87.2	-68.5		148.5	557.3	170.0	1.000033
58000.0	85.1	-67.6		144.2	558.5	168.8	1.000032
58500.0	83.0	-66.7		140.0	559.8	170.1	1.000031
59000.0	80.9	-65.8		136.0	561.0	177.3	1.000030
59500.0	79.0	-64.8		132.1	562.3	189.9	1.000029
60000.0	77.0	-63.9		128.3	563.5	222.0	1.000029
60500.0	75.1	-63.0		124.6	564.7	313.5	1.000028
61000.0	73.3	-62.1		121.0	566.0	355.4	1.000027
61500.0	71.5	-61.2		117.5	567.2	34.4	1.000026
62000.0	69.7	-60.4		114.2	568.3	51.9	1.000025
62500.0	68.1	-60.2		111.4	569.5	76.1	1.000025
63000.0	66.5	-60.0		108.6	568.8	94.3	1.000024

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79
ASCENSION NO. 284

UPPER AIR DATA
2410060284
S M R
TABLE 6 (CONT)

GEODETIC COORDINATES
32.48034 LAT UEG
106.42307 LONG DEG

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES DELMPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
63500.0	64.9	-59.8		105.9	569.0	106.9	15.7	1.000024
64000.0	63.3	-59.7		103.3	569.2	116.5	18.0	1.000023
64500.0	61.8	-59.5		100.8	569.5	123.7	20.8	1.000022
65000.0	60.3	-59.3		98.3	569.7	122.4	20.5	1.000022
65500.0	58.9	-59.1		95.9	569.9	120.5	20.0	1.000021
66000.0	57.5	-58.9		93.5	570.2	118.1	19.5	1.000021
66500.0	56.1	-58.8		91.2	570.4	114.3	18.6	1.000020
67000.0	54.8	-58.6		88.9	570.7	110.2	17.9	1.000020
67500.0	53.5	-58.4		86.7	570.9	108.2	17.5	1.000019
68000.0	52.2	-58.2		84.6	571.1	107.8	17.5	1.000019
68500.0	51.0	-58.0		82.5	571.4	107.5	17.4	1.000018
69000.0	49.7	-57.9		80.5	571.6	104.9	17.0	1.000018
69500.0	48.6	-57.6		78.5	571.9	102.1	16.6	1.000017
70000.0	47.4	-57.4		76.6	572.2	99.8	16.8	1.000017
70500.0	46.3	-57.2		74.7	572.5	97.8	18.0	1.000017
71000.0	45.2	-57.0		72.9	572.8	96.2	19.1	1.000016
71500.0	44.1	-56.8		71.1	573.1	96.1	19.5	1.000016
72000.0	43.1	-56.6		69.3	573.3	96.5	19.6	1.000015
72500.0	42.1	-56.3		67.6	573.6	96.7	19.8	1.000015
73000.0	41.1	-56.1		66.0	573.9	96.3	20.3	1.000015
73500.0	40.1	-55.9		64.3	574.2	96.0	20.8	1.000014
74000.0	39.2	-55.6		62.7	574.6	96.5	21.4	1.000014
74500.0	38.3	-55.1		61.1	575.3	98.1	22.2	1.000014
75000.0	37.4	-54.6		59.6	576.0	99.6	23.1	1.000013
75500.0	36.5	-54.1		58.1	576.6	101.7	23.0	1.000013
76000.0	35.7	-53.6		56.6	577.3	104.7	21.8	1.000013
76500.0	34.9	-53.1		55.2	577.9	107.9	20.7	1.000012
77000.0	34.0	-52.6		53.8	578.6	108.5	19.0	1.000012
77500.0	33.3	-52.1		52.4	579.2	106.9	17.0	1.000012
78000.0	32.5	-51.6		51.1	579.9	104.9	14.9	1.000011
78500.0	31.7	-51.1		49.8	580.5	98.7	15.2	1.000011
79000.0	31.0	-50.6		48.5	581.2	97.8	16.8	1.000011
79500.0	30.3	-50.1		47.3	581.8	80.6	18.8	1.000011
80000.0	29.6	-49.9		46.2	582.1	76.6	20.4	1.000010
80500.0	28.9	-49.9		45.1	582.1	74.0	22.1	1.000010
81000.0	28.2	-49.9		44.1	582.1	71.6	23.8	1.000010
81500.0	27.6	-49.9		43.1	582.1	73.5	24.9	1.000010
82000.0	27.0	-49.9		42.1	582.1	70.5	25.9	1.000009
82500.0	26.4	-49.9		41.1	582.1	79.5	26.9	1.000009
83000.0	25.8	-49.9		40.2	582.1	82.1	28.0	1.000009

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79
ASCENSION NO. 284

UPPER AIR DATA
2410060284
S M R

GEODETIC COORDINATES
32.48034 LAT UEG
106.42307 LON DEG

TABLE 6 (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
83500.0	25.2	-49.9		39.3	562.1	84.7	29.3	1.000009
84000.0	24.6	-49.9		38.4	582.1	87.1	30.5	1.000009
84500.0	24.0	-49.6		37.4	582.5	88.1	30.2	1.000008
85000.0	23.5	-49.1		36.5	583.2	88.3	28.9	1.000008
85500.0	23.0	-48.6		35.6	583.8	88.6	27.5	1.000008
86000.0	22.4	-48.0		34.7	584.5	88.6	26.7	1.000008
86500.0	21.9	-47.5		33.9	585.2	88.5	26.4	1.000008
87000.0	21.4	-47.0		33.0	585.8	88.3	26.0	1.000007
87500.0	20.9	-46.5		32.2	586.5	89.7	26.7	1.000007
88000.0	20.5	-46.0		31.4	587.1	92.6	28.9	1.000007
88500.0	20.0	-45.5		30.6	587.8	93.1	31.1	1.000007
89000.0	19.6	-45.4		29.9	588.0	97.7	33.2	1.000007
89500.0	19.1	-45.2		29.2	588.1	100.7	34.9	1.000007
90000.0	18.7	-45.1		28.6	588.3	103.3	36.8	1.000006
90500.0	18.3	-45.0		27.9	588.5	105.8	38.5	1.000006
91000.0	17.9	-44.8		27.3	588.7	108.5	37.3	1.000006
91500.0	17.5	-44.7		26.7	588.8	111.4	36.3	1.000006
92000.0	17.1	-44.5		26.0	589.0	114.4	35.4	1.000006
92500.0	16.7	-44.4		25.4	589.2	116.0	35.2	1.000006
93000.0	16.3	-44.3		24.9	589.4	117.4	35.1	1.000006
93500.0	16.0	-44.1		24.3	589.6	118.7	35.0	1.000005
94000.0	15.6	-44.0		23.7	589.7	119.4	34.8	1.000005
94500.0	15.3	-43.6		23.2	590.3	119.7	34.6	1.000005
95000.0	14.9	-43.1		22.6	590.8	119.9	34.3	1.000005
95500.0	14.6	-42.7		22.1	591.4	119.7	33.4	1.000005
96000.0	14.3	-42.3		21.6	592.0	118.4	31.6	1.000005
96500.0	14.0	-41.8		21.0	592.5	117.0	29.7	1.000005
97000.0	13.7	-41.4		20.5	593.1	115.0	28.0	1.000005
97500.0	13.4	-41.0		20.1	593.6	108.6	28.1	1.000004
98000.0	13.1	-40.5		19.6	594.2	102.2	28.5	1.000004
98500.0	12.8	-40.1		19.1	594.8	96.1	29.3	1.000004
99000.0	12.5	-39.6		18.7	595.3	93.4	30.6	1.000004
99500.0	12.2	-39.2		18.2	595.9	91.7	32.1	1.000004
100000.0	12.0	-38.8		17.8	596.4	90.2	33.6	1.000004
100500.0	11.7	-38.3		17.4	597.0			1.000004
101000.0	11.4	-37.9		17.0	597.5			1.000004
101500.0	11.2	-37.5		16.6	598.1			1.000004

STATION ALTITUDE 3997.30 FEET MSL
29 AUG. 79
ASCENSION I.O. 204

MANDATORY LEVELS
2410060284
S M R
TABLE 7

GEODETTIC COORDINATES
32.44034 LAT DEG
106.42307 LON DEG

PRESSURE GEOPOTENTIAL		TEMPERATURE		REL. HUM. PERCENT	WIND DATA	
MILLIBARS	FEET	AIR DEGREES	DEWPOINT CENTIGRADE		DIRECTION DEGREES(TN)	SPEED KNOTS
850.0	4897.	23.6	6.4	33.	41.3	5.0
800.0	6626.	21.6	2.6	29.	13.0	1.8
750.0	8452.	18.6	-0	28.	355.4	1.9
700.0	10376.	13.6	-2.3	33.	26.1	5.6
650.0	12404.	8.2	-4.8	39.	71.0	6.5
600.0	14551.	2.4	-5.7	55.	118.9	12.3
550.0	16835.	-3.8	-8.5	70.	136.2	13.2
500.0	19284.	-7.9	-16.0	52.	178.7	11.4
450.0	21952.	-12.2	-20.5	50.	177.3	11.8
400.0	24873.	-18.4	-26.0	51.	202.8	14.9
350.0	28101.	-25.0	-35.3	37.	216.8	12.2
300.0	31711.	-33.8	-39.3	57.	236.8	26.5
250.0	35865.	-40.7			250.1	54.7
200.0	40724.	-52.4			250.3	53.1
175.0	43512.	-59.4			249.9	43.4
150.0	46651.	-63.7			232.8	30.9
125.0	50269.	-69.4			246.9	19.0
100.0	54631.	-71.0			205.0	8.6
80.0	59013.	-65.3			181.0	7.3
70.0	61711.	-60.4			48.2	9.7
60.0	64871.	-59.3			122.1	20.5
50.0	68631.	-57.9			105.7	17.1
40.0	73260.	-55.9			96.0	20.8
30.0	79356.	-49.9			78.9	19.4
25.0	83267.	-49.9			85.2	29.5
20.0	88096.	-45.5			95.0	30.9
15.0	94415.	-43.2			119.8	34.4